

Kaiflex PROTECT ALU-TEC



Samolepicí ST hadice s povrchovou ALU-TEC ochranou

Měď		Ocel		Průměr vnitřní	tloušťka izolace / cena Kč/ balení					
jmen.		jmen.			13mm		19mm		25mm	
světlost	coul	světlost		průměr	m/	Kč/	m/	Kč/	m/	Kč/
DN		DN		izolace	kart.	bm	kart.	bm	kart.	bm
10	1/4	8		15	77	246,0	43	316,9		
15	3/8	10		18	65	250,8	39	324,9	25	389,5
20	1/2	15		22	55	258,5	37	334,4	21	428,7
25	3/4	20		28	43	278,8	29	360,9	20	455,5
32	1	25		35	38	299,7	24	395,8	16	484,2
	1 1/4	32		42	28	328,1	20	422,4	12	528,3
				45	26	337,5	17	443,0		
	1 1/2	40		48	24	348,4	15	463,6	12	562,8
		50		54	23	391,0	15	534,6	11	604,0
				57	22	411,5	14	548,6		
	2	50		60	20	433,7	14	564,7	11	689,5
				64	20	449,3	14	586,6	9	725,3
				70	20	479,3	14	613,2	9	760,2
65	2 1/2	65		76	17	496,8	14	632,1	9	783,3
				80	15	515,8	13	667,0		
80	3	80		89	15	534,6	11	701,6	7	858,0
100				108	14	610,4			5	977,6
100	4	100		114	14	643,2	9	845,2	5	1031,7
				125	10	706,5	9	924,6		
		125		140	9	791,6	5	1037,9	3	1267,8
				160	8	903,2	4	1185,6		

Kaiflex Protect ALU-TEC deska / role					Kaiflex Protect ALU-TEC deska / role samolepicí		
objednací číslo	tloušťka izolace	šířka role	balení m ²	Kč/m ²	objednací číslo	tloušťka izolace	Kč/m ²
4000794	10	1m	20	1055,6	42761	20	1153
4000795	13	1m	14	1128,4	42762	14	1220
4000796	19	1m	10	1204,3	42763	10	1290
4000797	25	1m	8	1521,5	42764	8	1578
4000798	32	1m	6	1606,8	42765	6	1655
4006539	50	1m	6	2576,0		6	2771

- * nekovový systém opláštění
- * odolný vůči UV záření a povětrnostním vlivům
- * opticky vytříbený kovový vzhled
- * chrání spolehlivě před mechanickým poškozením
- * jednoduchá montáž hadic díky samolepicímu spoji



Ceny se rozumí FCA Krnov, bez DPH a dopravy